

5623UX BRUNEI

Recessed lightbar for public spaces. Length on request (max = 2000mm, min = 150mm), can be installed individually or as a continuous line. Clips in with no screws for vandal-proof installation.

APPLICATIONS:



- Decorative or safety marker-lighting for public spaces
- Highlight facades

CARACTERISTICS

DMX control with lightbar configuration after installation.
Uniform window

- Vandalproof profiled organic glass
- Colourless anodised aluminium profile (except 5620X)
- Recessed
- 2 Profiled mounts with extruded-aluminium accessories for continuous line or individual installation.
 - Ground-recessed version with internal space for running cable and connectors
 - Compact surface-mounted
- Version RGB options available

80 leds/m for RGB et 120 leds/m for Mono



Number of LEDs	120, 80
Type of LEDs	120° SMD LEDs (S), SMD trichro (A)
Color(s)	Warm white 2700K (F), Warm white 3000K (E), Neutral white 4000K (N), Cool white 6000K (W), Red (R), Amber (O), Green (V), Blue (L), RVB (T)

Select your specific requirements with our product configurator, by filtering technical criteria at the following link:
<http://www.lec.fr/5623uxz-brunei-r2390>

APPLICATION

- Marker-lighting

CONFIGURATEUR.EMPLACEMENT

- Wall recessed
- Ground flush recessed fittings
- Ground recessed fittings
- Pavements sides
- Masts
- Handrails

CARACTERISTICS

Weight : 730 g/m

Options of luminous effects

- RGB options
- Non adjustable
- Beam with various openings
- Flat homogeneous window (optional)
- Colour control system (optional)

Power supply - Control

- Cable length: **Connector**
- Integrated** : 24V-DMX

Material

- AL** Anodised glazed aluminium
- VO** Vandalism-proof organic glass

Mechanical strength - Waterproofness

- Withstands random all vehicles traffic
- IK10 60J** Resists impacts up to 60 joules (IK10)
- IP68** Tight for extended immersion